

Technical Data Sheet

3mm 2pcs Circuit Board Indicator

A2774B/UYSYGW/S530-A3



Features :

- Low power consumption
- High efficiency and low cost
- Good control and free combinations on the colors of LED lamps
- Good lock and easy to assembly
- Stackable and easy to assembly
- Stackable vertically and easy to assembly
- Versatile mounting on P.C board or panel
- Stackable horizontally and easy to assembly
- Pb free
- The product itself will remain within RoHS compliant version

Descriptions :


- ARRAY=Plastic Holder+Combinations of Lamps
- The array will easily mount the applicable lamps on any panel up to

Applications :

- 1.Used as indicators of indicating the Degree, Functions, Positions etc, in electronic instruments.

PART NO.	Chip		Lens Color
	Material	Emitted Color	
264-2UYSYGW/S530-A3/B/F45-85	AlGaInP	Super Yellow	White Diffused
	AlGaInP	Super Yellow Green	

Package Dimensions



- Notes: 1.All dimensions are in millimeters, tolerance is 0.25mm except being specified
2.Lead spacing is measured where the lead emerge from the package

Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Forward Current	IF	UY/S530	25
		SYG/S530	25
Operating Temperature	Topr	-40 to +85	$^\circ\text{C}$
Storage Temperature	Tstg	-40 to +100	$^\circ\text{C}$
Soldering Temperature	Tsol	260 ± 5	$^\circ\text{C}$
Electrostatic Discharge	ESD	UY/S530	2000
		SYG/S530	2000
Power Dissipation	Pd	UY/S530	60
		SYG/S530	60
Reverse Voltage	VR	5	V

Note: *1:Soldering time ≤ 5 seconds.

Technical Data Sheet

3mm 2pcs Circuit Board Indicator

A2774B/UYSYGW/S530-A3

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol		Condition	Min	Typ	Max	Unit
Luminous Intensity	UY/S530	IV	I _F = 20 mA	16	32	/	mcd
	SYG/S530			16	32	/	
Peak Wavelength	UY/S530	λ p	I _F = 20 mA	/	591	/	nm
	SYG/S530			/	575	/	
Dominant Wavelength	UY/S530	λ d	I _F = 20 mA	/	589	/	nm
	SYG/S530			/	573	/	
Viewing Angle	2 θ 1/2		I _F = 20 mA	/	100	/	deg
Spectrum Radiation Bandwidth	UY/S530	△ λ	I _F = 20 mA	/	15	/	nm
	SYG/S530			/	20	/	
Forward Voltage	UY/S530	VF	I _F = 20 mA	/	2.0	2.4	V
	SYG/S530			/	2.0	2.4	
Reverse Current	UY/S530	IR	V _R = 5 V	/	/	10	μ A
	SYG/S530			/	/	10	







Technical Data Sheet

3mm 2pcs Circuit Board Indicator

A2774B/UYSYGW/S530-A3







Typical Electro-Optical Characteristic Curves:

(UY)



■ Typical Electro-Optical Characteristic Curves:

(SYG)



Technical Data Sheet

3mm 2pcs Circuit Board Indicator

A2774B/UYSYGW/S530-A3

■ Reliability test items and conditions:

The reliability of products shall be satisfied with items listed below.

Confidence level : 97%

LTPD : 3%

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Failure Judgment Criteria	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	10 SEC	76 PCS	$I_v \leq I_{vt} * 0.5$ or $V_f \geq U$ or $V_f \leq L$	0/1
2	Temperature Cycle	H : +100°C 15min § 5 min L : -40°C 15min	300 CYCLES	76 PCS		0/1
3	Thermal Shock	H : +100°C 5min § 10 sec L : -10°C 5min	300 CYCLES	76 PCS		0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS		0/1
5	Low Temperature Storage	TEMP : -40°C	1000 HRS	76 PCS		0/1
6	DC Operating Life	TEMP : 25°C I _F = 20mA	1000 HRS	76 PCS		0/1
7	High Temperature / High Humidity	85°C / 85% RH	1000 HRS	76 PCS		0/1

Note : I_{vt} : To test I_v value of the chip before the reliability test

I_v : The test value of the chip that has completed the reliability test

U : Upper Specification Limit

L : Lower Specification Limit

Technical Data Sheet

3mm 2pcs Circuit Board Indicator


A2774B/UYSYGW/S530-A3

Packing Quantity Specification

1.500PCS/1plate , 4 plates/1Box

2. 10Boxes/1Carton

Label Form Specification



The diagram shows a rectangular label with the following elements:

- Top left: A circle containing the symbol Pb .
- Top center: A rectangle containing the word "EVERLIGHT".
- Top right: A circle containing the letter "X".
- Below Pb : "CPN:" and "P/N:" followed by a barcode.
- Below the first barcode: "A2774B/UYSYGW/S530-A3".
- Below the product code: "QTY:" followed by a barcode.
- Below the second barcode: "LOT NO:" followed by a barcode.
- Below the third barcode: "Reference:" followed by a barcode.
- Below the product code: "CAT:" followed by a space.
- Below "CAT:": "HUE:" followed by a space.
- Below "HUE:": "REF:" followed by a space.
- Bottom right: A rectangle containing the text "RoHS".

CPN: Customer' s Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks

HUE: Dominant Wavelength

REF: Reference

LOT No: Lot Number

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don' t reproduce or cause anyone to reproduce them without EVERLIGHT' s consent.

EVERLIGHT ELECTRONICS CO., LTD.

Office: No 25, Lane 76, Sec 3, Chung Yang Rd,
Tucheng, Taipei 236, Taiwan, R.O.C

Tel: 886-2-2267-2000, 2267-9936

Fax: 886-2267-6244, 2267-6189, 2267-6306

<http://www.everlight.com>