
EVERLIGHT AMERICAS

DATASHEET

Technical Data Sheet
Opto Interrupter
EAITRBA3

Features



- Fast response time
- High analytic
- High sensitivity
- Cut-off visible wavelength λP=940nm
- Pb Free
- This product itself will remain within RoHS compliant version.

Description

The **EAITRBA3** consists of an infrared emitting Diode and a silicon phototransistor encased in a black Thermo-plastic housing. The advantage of the device is the small package. Phototransistor receives radiation from the IR LED only, and avoids the noise from ambient light

Applications

- Camera
- Copier
- Scanner
- Non-contact Switching
- For Direct PC Board

Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx

Device Selection Guide

Device No.	Chip Material	LENS COLOR
IR	GaAlAs	Water clear
PT	Silicon	Black

Absolute Maximum Ratings (Ta=25℃)

Parameter		Symbol	Ratings	Unit
Input	Power Dissipation at(or below) 25℃ Free Air Temperature	Pd	75	mW
	Reverse Voltage	V_R	5	V
	Forward Current	I_F	50	mA
	Peak Forward Current (*1) Pulse width ≦100μs, Duty cycle=1%	I_{FP}	1	A
Output	Collector Power Dissipation	P_C	75	mW
	Collector Current	I_C	20	mA
	Collector-Emitter Voltage	B V_{CEO}	30	V
	Emitter-Collector Voltage	B V_{ECO}	5	V
Operating Temperature		Topr	-25~+85	℃
Storage Temperature		Tstg	-40~+85	℃
Lead Soldering Temperature (*2) (1/16 inch form body for 5 seconds)		Tsol	260	℃

Notes: (＊1) tw=100 μsec. , T=10 msec. (＊2) t=5 Sec



Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx



Electro-Optical Characteristics (Ta=25℃)

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Input	Forward Voltage	V_F	-	1.2	1.6	V	I_F=20mA
	Reverse Current	I_R	-	-	10	μA	V_R=5V
	Peak Wavelength	λ_P	-	940	-	nm	I_F=20mA
Output	Dark Current	I_{CEO}	-	-	100	nA	V_{CE}=10V,Ee=0mW/cm^2
	C-E Saturation Voltage	$V_{CE(sat)}$	-	-	0.4	V	I_C=2mA,Ee=1mW/cm
Collector Current(＊3)		$I_{C(ON)}$	0.3	-	-	mA	V_{CE}=5V,I_F=10mA
		$I_{C(OFF)}$	-	-	1	μA	
Response Time	Rise Time	t_R	-	15	-	μs	V_{CE}=2V I_C=1mA R_L=1KΩ
	Fall Time	t_F	-	15	-	μs	

Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx

Typical Electrical/Optical/Characteristics Curves for IR


Collector Power Dissipation vs. Ambient Temperature	Spectral Distribution
	

Peak Emission Wavelength vs . Ambient Temperature	Forward Current vs. Forward Voltage
	


Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx

Typical Electro/Optical/Characteristics Curves for PT


Collector Power Dissipation vs. Ambient Temperature




Collector Dark Current vs. Ambient Temperature





Relative Collector Current vs. Ambient Temperature



Collector Current vs. Irradiance



Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx

Collector Dark Current vs. Ambient Temperature	Collector Current vs. Collector-Emitter Voltage
	

Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx


Reliability Test Item And Condition


The reliability of products shall be satisfied with items listed below.
Confidence level：90%
LTPD：10%

NO.	Item	Test Condition	Test Hours/ Cycle	Sample Size	Failure Judgement Criteria	Ac/Re
1	**Solder Heat**	TEMP : 260℃ ± 5 ℃	10 sec	22 PCs		0/1
2	**Temperature Cycle**	H : +100℃ 15 mins 5 min L : -40℃ 15 min	300 cycle	22 PCs	Ic(on)≦L×0.8	0/1
3	**Thermal Shock**	H : +100℃ 5 min 10 sec L : -10℃ 5 min	300 cycle	22 PCs	L :Lower specification limit	0/1
4	**High Temperature Storage**	TEMP. : +100℃	1000 hrs	22 PCs		0/1
5	**Low Temperature Storage**	TEMP. : -40℃	1000 hrs	22 PCs		0/1
6	**DC Operating Life**	V_{CE}=5V I_F=20mA	1000 hrs	22 PCs		0/1
7	**High Temperature / High Humidity**	85℃ / 85% R.H.	1000 hrs	22 PCs		0/1


Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx


Package Dimension






1:Anode
2:Cathode
3:Collector
4:Emillter








A-A' SECTION

Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx

Packing Quantity Specification

1.150PCS/1Bag, 5Bag/1Box
2. 10Boxes/1Carton

Label Form Specification



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number
- X: Month
- Reference: Identify Label Number

Notes

1. Above specification may be changed without notice. EVERLIGHT Americas will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT Americas assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT Americas corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT Americas consent.

Copyright © 2010, Everlight Americas Inc. Release Date : 10.18.2013. Issue No:DIR-000xxx