
EVERLIGHT AMERICA

DATASHEET

SMD ▪ B

EASR3212BA2



CONFIDENTIAL

Features

- Package in 8mm tape on 7″ diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Mono-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

- The SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing

Copyright © 2010, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1

R
LifecyclePhase:Developing()
Expired Period: Forever

density, reduced storage space and finally smaller equipment to be obtained.

- Besides, lightweight makes them ideal for miniature applications. etc.

Applications

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

Device Selection Guide

Chip Materials	Emitted Color	Resin Color
InGaN	Pastel sky blue	Green Diffused

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Unit
Reverse Voltage	V_R	5	V
Forward Current	I_F	10	mA
Peak Forward Current (Duty 1/10 @1KHz)	I_{FP}	100	mA
Power Dissipation	Pd	40	mW
Electrostatic Discharge	ESD_{HBM}	150	V
Operating Temperature	T_{opr}	-40 ~ +85	℃
Storage Temperature	Tstg	-40 ~ +90	℃
Soldering Temperature	Tsol	Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

CONFIDENTIAL

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing() Expired Period: Forever

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	28.5	-----	112	mcd	I_F=5mA
Viewing Angle	$2\theta_{1/2}$	-----	140	-----	deg	
Forward Voltage	V_F	2.5	-----	3.3	V	
Reverse Current	I_R	-----	-----	50	μA	V_R=5V

Note:
1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Forward Voltage ±0.1V

CONFIDENTIAL

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
LifecyclePhase:Developing() Expired Period: Forever

CONFIDENTIAL

Bin Range of Luminous Intensity

Bin Code	Min.	Max.	Unit	Condition
N	28.5	45.0	mcd	I_F =5mA
P	45.0	72.0		
Q	72.0	112		

Bin Range Of Luminous Voltage

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing() Expired Period: Forever

Bin Code	Min.	Max.	Unit	Condition
1	2.5	2.7	V	I_F =5mA
2	2.7	2.9		
3	2.9	3.1		
4	3.1	3.3		

Note:
1.Tolerance of Luminous Intensity: ±11%
2.Tolerance of Forward Voltage ±0.1V

CONFIDENTIAL

T Chromaticity Coordinates Specifications for Bin Grading

Bin Code	CIE_x	CIE_y	Condition
A	0.200	0.340	I_F =5mA
	0.185	0.340	
	0.180	0.300	
	0.195	0.300	
B	0.205	0.380	
	0.190	0.380	
	0.185	0.340	
	0.200	0.340	

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing()
Expired Period: Forever

C	0.215	0.340
	0.200	0.340
	0.195	0.300
	0.210	0.300
D	0.220	0.380
	0.205	0.380
	0.200	0.340
	0.215	0.340

Notes:

1.The C.I.E. 1931 chromaticity diagram (Tolerance ±0.01).


2.The products are sensitive to static electricity and care must be fully taken when handling products.

.

CONFIDENTIAL


Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing()
Expired Period: Forever


CIE Chromaticity Diagram





Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing() Expired Period: Forever


Typical Electro-Optical Characteristics Curves


















Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing() Expired Period: Forever


Package Outline Dimensions











Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

Note: Tolerances unless mentioned ±0.1mm. Unit = mm

CONFIDENTIAL

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com

R
LifecyclePhase:Developing()
Expired Period: Forever


Moisture Resistant Packing Materials

Label Explanation



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates & Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number

Reel Dimensions




CONFIDENTIAL

Note: The tolerances unless mentioned is ±0.1mm ,Unit = mm

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing()
Expired Period: Forever


Carrier Tape Dimensions: Loaded quantity2000 PCS per reel



Note: The tolerances unless mentioned is ±0.1mm ,Unit = mm

Moisture Resistant Packaging

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
LifecyclePhase:Developing() Expired Period: Forever



Precautions For Use

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 After opening the package: The LEDs should be kept at 30℃ or less and 60%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30℃ or less and 60% RH or less.

If unused LEDs remain, it should be stored in moisture proof packages

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.


Baking treatment : 60±5℃ for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile

CONFIDENTIAL

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing() Expired Period: Forever



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

4.Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350℃ for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5.Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
LifecyclePhase:Developing() Expired Period: Forever

Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

CONFIDENTIAL

Copyright © 2016, Everlight All Rights Reserved. Release Date : Jan.22.2016. Issue No: DSE-0014742 Rev.1 www.everlight.com
R
LifecyclePhase:Developing()
Expired Period: Forever