


### SMD LED EASV3015RGYA1



#### Features

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Multi-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.

#### Descriptions

This SMD LED is much smaller than lead frame components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained. Besides, lightweight makes them ideal for miniature applications. etc.

#### Applications

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

## Device Selection Guide

Chip		Emitted Color	Resin Color
Type	Material		
R6	AlGaInP	Brilliant Red	Water Clear
Y2	AlGaInP	Brilliant Yellow	
G6	AlGaInP	Brilliant Yellow Green	

## Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Reverse Voltage	V <sub>R</sub>	5	V
Forward Current	I <sub>F</sub>	25	mA
Peak Forward Current (Duty 1/10 @1KHz)	I <sub>FP</sub>	R6:60 Y2:60 G6:60	mA
Power Dissipation	P <sub>d</sub>	R6:60 Y2:60 G6:60	mW
Electrostatic Discharge (HBM)	ESD	R6:2000 Y2:2000 G6:2000	V
Operating Temperature	T <sub>opr</sub>	-40 ~ +85	°C
Storage Temperature	T <sub>stg</sub>	-40 ~ +90	°C
Soldering Temperature	T <sub>sol</sub>	Reflow Soldering : 260 °C for 10 sec. Hand Soldering : 350 °C for 3 sec.	

### Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	R6	45.0		112.0		If=20mA
	Iv Y2	45.0	----	112.0	mcd	
	G6	45.0		112.0		
Viewing Angle	2 $\theta$ 1/2	-----	100	-----	deg	
Peak Wavelength	R6		632			
	$\lambda$ p Y2	-----	591	-----	nm	
	G6		575			
Dominant Wavelength	R6	617.5		633.5		If=20mA
	$\lambda$ d Y2	585.5	-----	594.5	nm	
	G6	569.5		575.5		
Spectrum Radiation Bandwidth	R6		20			
	$\Delta \lambda$ Y2	-----	15	-----	nm	
	G6		20			
Forward Voltage	R6	1.7	2.0	2.4		V
	V <sub>F</sub> Y2	1.7	2.0	2.4		
	G6	1.7	2.0	2.4		
Reverse Current	R6			10		$\mu$ A
	I <sub>R</sub> Y2	-----	-----	10		
	G6			10		
						V <sub>R</sub> =5V

### Notes:

- 1.Tolerance of Luminous Intensity  $\pm 11\%$
- 2.Tolerance of Dominant Wavelength  $\pm 1\text{nm}$

## Bin Range Of Luminous Intensity

### R6

Bin	Min	Max	Unit	Condition
P	45.0	72.0	mcd	$I_F=20\text{mA}$
Q	72.0	112		

### Y2

Bin	Min	Max	Unit	Condition
P	45.0	72.0	mcd	$I_F=20\text{mA}$
Q	72.0	112		

### G6

Bin	Min	Max	Unit	Condition
P	45.0	72.0	mcd	$I_F=20\text{mA}$
Q	72.0	112		

### Notes:

Tolerance of Luminous Intensity  $\pm 11\%$

### Reliability Test Items And Conditions

The reliability of products shall be satisfied with items listed below.

Confidence level : 90%

LTPD : 10%

No.	Items	Test Condition	Test Hours/Cycles	Sample Size	Ac/Re
1	Reflow Soldering	Temp. : 260°C±5°C Min. 5sec.	6 Min.	22 PCS.	0/1
2	Temperature Cycle	H : +100°C 15min ∫ 5 min L : -40°C 15min	300 Cycles	22 PCS.	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	300 Cycles	22 PCS.	0/1
4	High Temperature Storage	Temp. : 100°C	1000 Hrs.	22 PCS.	0/1
5	Low Temperature Storage	Temp. : -40°C	1000 Hrs.	22 PCS.	0/1
6	DC Operating Life	I <sub>F</sub> = 20 mA	1000 Hrs.	22 PCS.	0/1
7	High Temperature / High Humidity	85°C / 85%RH	1000 Hrs.	22 PCS.	0/1

## Bin Range Of Dom. Wavelength

### R6

Groups	Bin	Min	Max	Unit	Condition
A	E4	617.5	621.5	nm	I <sub>F</sub> =20mA
	E5	621.5	625.5		
	E6	625.5	629.5		
	E7	629.5	633.5		

### Y2

Groups	Bin	Min	Max	Unit	Condition
A	D3	585.5	588.5	nm	I <sub>F</sub> =20mA
	D4	588.5	591.5		
	D5	591.5	594.5		



### G6

Groups	Bin	Min	Max	Unit	Condition
M	C16	569.5	571.5	nm	I <sub>F</sub> =20mA
	C17	571.5	573.5		
	C18	573.5	575.5		


### Notes:

Tolerance of Dominant Wavelength  $\pm 1\text{nm}$



## Package Outline Dimensions



Polarity









For reflow soldering (propose)









**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

## Typical Electro-Optical Characteristics Curves R6











## Typical Electro-Optical Characteristics Curves Y2



## Typical Electro-Optical Characteristics Curves G6




## Label explanation


**CAT:** Luminous Intensity Rank

**HUE:** Dom. Wavelength Rank

**REF:** Forward Voltage Rank




## Reel Dimensions




**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

### Carrier Tape Dimensions: Loaded quantity 2000 PCS per reel



**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

### Moisture Resistant Packaging



## Precautions For Use

### 1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change ( Burn out will happen ).

### 2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package: The LEDs should be kept at 30°C or less and 90%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30°C or less and 60% RH or less.


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment :  $60\pm5^{\circ}\text{C}$  for 24 hours.

### 3. Soldering Condition

#### 3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.

3.4 After soldering, do not warp the circuit board.

#### 4.Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

#### 5.Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.

