


SMD ■ B EAST3227YGA0



Features

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Multi-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.
- Compliance with EU REACH
- Compliance Halogen Free .(Br <900 ppm ,Cl <900 ppm , Br+Cl < 1500 ppm).

Description

The EAST3227YGA0 SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained. Besides, lightweight makes them ideal for miniature applications. etc.

Applications

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

Device Selection Guide

Code	Chip Materials	Emitted Color	Resin Color
Y1	GaAsP/GaP	Yellow	Water Clear
G5	GaP	Yellow Green	

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Code	Rating	Unit
Reverse Voltage	V _R		5	V
Forward Current	I _F	Y1	30	mA
		G5	30	
Peak Forward Current (Duty 1/10 @1KHz)	I _{FP}	Y1	60	mA
		G5	60	
Power Dissipation	Pd	Y1	100	mW
		G5	100	
Operating Temperature	T _{opr}		-40 ~ +85	℃
Storage Temperature	T _{stg}		-40 ~ +90	℃
Electrostatic Discharge	ESD _{HBM}	Y1	2000	V
		G5	2000	
Soldering Temperature	T _{sol}		Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Code	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v	Y1	5.0	-----	13.0	mcd	
		G5	8.0	-----	20.0		
Viewing Angle	2θ _{1/2}		-----	140	-----	deg	
Peak Wavelength	λ _p	Y1	-----	585	-----	nm	
		G5	-----	570	-----		
Dominant Wavelength	λ _d	Y1	584.0	-----	593.0	nm	I _F =20mA
		G5	566.0	-----	572.0		
Spectrum Radiation Bandwidth	Δλ	Y1	-----	35	-----	nm	
		G5	-----	30	-----		
Forward Voltage	V _F	Y1	1.7	2.0	2.4	V	
		G5	1.7	2.0	2.4		
Reverse Current	I _R	Y1	-----	-----	10	μA	V _R =5V
		G5	-----	-----	10		

Note:

1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Dominant Wavelength: ±1nm

Bin Range of Luminous Intensity Y1

Bin Code	Min.	Max.	Unit	Condition
1	5.0	8.0	mcd	I _F =20mA
2	8.0	13.0		

Bin Range of Luminous Intensity G5

Bin Code	Min.	Max.	Unit	Condition
1	8.0	13.0	mcd	I _F =20mA
2	13.0	20.0		

Bin Range Of Dom. Wavelength Y1

Bin Code	Min.	Max.	Unit	Condition
A	584.0	589.0	nm	I _F =20mA
B	589.0	593.0		







Bin Range Of Dom. Wavelength G5

Bin Code	Min.	Max.	Unit	Condition
A	566.0	569.0	nm	I _F =20mA
B	569.0	572.0		







Note:

- 1.Tolerance of Luminous Intensity: $\pm 11\%$
- 2.Tolerance of Dominant Wavelength $\pm 1\text{nm}$


Typical Electro-Optical Characteristics Curves Y1




Typical Electro-Optical Characteristics Curves G5




Package Dimension




Top



Side




Bottom



Polarity


Recommend soldering pad



Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.


Note: Tolerances unless mentioned ± 0.1 mm. Unit = mm

Moisture Resistant Packing Materials Label Explanation




- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Chromaticity Coordinates
- REF: Forward Voltage Rank
- LOT No: Lot Number

Reel Dimensions




Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$, Unit = mm

Carrier Tape Dimensions: Loaded quantity 2000 PCS per reel



Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$, Unit = mm

Moisture Resistant Packaging



Precautions For Use

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 After opening the package: The LEDs should be kept at 30°C or less and 60%RH or less.

2.3 The LEDs should be used within 168 hours (7days) after opening the package .


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment : 60±5°C for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.


3.4 After soldering, do not warp the circuit board.

4. Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5. Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

EVERLIGHT